

Schottky Barrier Rectifier

SS54A

SMA



Cathode  **Anode**

Features

- Low forward voltage drop
- Low power losses
- High efficiency operation
- Lead Free Finish, RoHS Compliant

Applications

- DC/DC Converters
- AC/DC Adaptors
- Switching Power Supplies
- Freewheeling Diodes

Maximum ratings and electrical characteristics (T_J = 25°C unless otherwise noted)


Parameter			Symbol	Limit		Unit
Maximum repetitive peak reverse voltage			VRRM	40		V
Maximum average forward rectified current			IF(AV)	5		A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load			IFSM	120		A
Operating junction and storage temperature range			TJ, TSTG	-55 to +150		°C
Typical thermal resistance			RθJA	65		°C/W
Instantaneous forward voltage			VF(1)	TYP.	MAX.	V
	IF=3A	TJ=25°C		0.55	0.60	
	IF=3A	TJ=125°C		0.50	-	
Instantaneous reverse current at rated reverse voltage		TJ=25°C	IR(2)	10	100	μA
		TJ=125°C		10	-	mA

Notes:


(1) Pulse test: 300 μs pulse width, 1 % duty cycle

(2) Pulse test: Pulse width ≤ 40 ms


RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)




Current Derating, Case



Maximum Repetitive Surge Current




Typical Forward Voltage



Typical Reverse Current


PACKAGE OUTLINE DIMENSIONS

SMA



UNIT		A	D	E	H _E	c	e	g	b	a
mm	max	2.2	4.5	2.7	5.2	0.31	1.6	1.5	0.2	0.3
	min	1.9	4.0	2.3	4.7	0.15	1.3	0.9	0.05	
mil	max	87	181	106	205	12	63	59	7.9	12
	min	75	157	91	185	6	51	35	2	

Marking Information



①Product model : SS54A

②PDC information :

Y X WW

WW:Week code(01 to 53)

X:Internal identification code

Y:Year code(ex:0=2020)